

CrystalMark	39128
ALU	6630
Fibonacci	1745
Napierian	1603
Eratosthenes	1593
QuickSort	1667
FPU	6438
MikoFPU	1604
RandMeanSS	1513
FFT	1681
Mandelbrot	1618
MEM	7463
Read	3696.96 MB/s ( 3696 )
Write	1428.22 MB/s ( 1428 )
Read/Write	1434.73 MB/s ( 1434 )
Cache	8833.94 MB/s ( 883 )
HDD	5301
Read	38.81 MB/s ( 1552 )
Write	38.29 MB/s ( 1531 )
RandomRead512K	21.28 MB/s ( 851 )
RandomWrite512K	21.41 MB/s ( 856 )
RandomRead 64K	5.19 MB/s ( 207 )
RandomWrite 64K	7.61 MB/s ( 304 )
GDI	5589
Text	903
Square	1530
Circle	1834
BitBlt	1322
D2D	1940
Sprite 10	70.77 FPS ( 7 )
Sprite 100	65.09 FPS ( 65 )
Sprite 500	47.92 FPS ( 239 )
Sprite 1000	35.96 FPS ( 359 )
Sprite 5000	12.14 FPS ( 607 )
Sprite 10000	6.63 FPS ( 663 )
OGL	5767
Scene 1	2358
Lines (x1000)	( 348030)
Scene 2 CPU	( 64)
Scene 2 Score	3409
Polygons (x1000)	( 192493)
Scene 2 CPU	( 128)

## System Information

OS	Windows XP Home Service Pack 2 [5.1 Build 2600]
Display Mode	1280 x 1024 32bit 60Hz
Memory	1024 MB

## BIOS

Vendor	Award Software International, Inc.
Caption	Award Modular BIOS v6.00PG
Version	GBT - 42302e31
Date	2005/08/19

## SM BIOS

Caption	F13
Version	2.3

## Mother

Vendor	Gigabyte Technology Co., Ltd.
Product	8IK1100
Version	

## Computer System

Vendor	GBT_
Product	AWRDACPI

## CPU Information

CPU Name	Intel Pentium 4 HT (Northwood)	
Vendor String	GenuineIntel	
Name String	Intel(R) Pentium(R) 4 CPU 2.40GHz	
Platform	Socket 478	
CPU Type	Original OEM processor	
Number(Logical)	2	
Hyper-Threading	2	
Family	F	
FamilyEx	00	
Model	2	
Stepping	9	
BrandID	09	
APIC	00	
Feature	MMX SSE SSE2 HTT	
	Current	Original
Clock	2411.65 MHz	2400.00 MHz
System Clock	200.97 MHz	200.00 MHz
System Bus	803.88 MHz	800.00 MHz