

| | |
|------------------|-----------------------|
| CrystalMark | 55929 |
| ALU | 9920 |
| Fibonacci | 4226 |
| Napierian | 1838 |
| Eratosthenes | 1532 |
| QuickSort | 2302 |
| FPU | 10565 |
| MikoFPU | 1750 |
| RandMeanSS | 4907 |
| FFT | 2107 |
| Mandelbrot | 1779 |
| MEM | 8452 |
| Read | 4141.46 MB/s (4141) |
| Write | 1674.05 MB/s (1674) |
| Read/Write | 1684.15 MB/s (1684) |
| Cache | 9310.38 MB/s (931) |
| HDD | 9412 |
| Read | 69.02 MB/s (2760) |
| Write | 64.68 MB/s (2587) |
| RandomRead512K | 38.67 MB/s (1546) |
| RandomWrite512K | 39.48 MB/s (1579) |
| RandomRead 64K | 8.85 MB/s (354) |
| RandomWrite 64K | 14.66 MB/s (586) |
| GDI | 7289 |
| Text | 1216 |
| Square | 1888 |
| Circle | 1697 |
| BitBlt | 2488 |
| D2D | 3256 |
| Sprite 10 | 381.24 FPS (38) |
| Sprite 100 | 308.27 FPS (308) |
| Sprite 500 | 141.14 FPS (705) |
| Sprite 1000 | 72.18 FPS (721) |
| Sprite 5000 | 14.82 FPS (741) |
| Sprite 10000 | 7.43 FPS (743) |
| OGL | 7035 |
| Scene 1 | 4940 |
| Lines (x1000) | (835911) |
| Scene 2 CPU | (128) |
| Scene 2 Score | 2095 |
| Polygons (x1000) | (103445) |
| Scene 2 CPU | (64) |

System Information

| | |
|--------------|---|
| OS | Windows XP Home Service Pack 2 [5.1 Build 2600] |
| Display Mode | 1280 x 1024 32bit 60Hz |
| Memory | 1024 MB |

BIOS

| | |
|---------|------------------------------------|
| Vendor | Award Software International, Inc. |
| Caption | Award Modular BIOS v6.00PG |
| Version | GBT - 42302e31 |
| Date | 2005/08/19 |

SM BIOS

| | |
|---------|-----|
| Caption | F13 |
| Version | 2.3 |

Mother

| | |
|---------|-------------------------------|
| Vendor | Gigabyte Technology Co., Ltd. |
| Product | 8IK1100 |
| Version | |

Computer System

| | |
|---------|----------|
| Vendor | GBT_ |
| Product | AWRDACPI |

CPU Information

| | | |
|-----------------|-----------------------------------|-------------|
| CPU Name | Intel Pentium 4 HT (Prescott) | |
| Vendor String | GenuineIntel | |
| Name String | Intel(R) Pentium(R) 4 CPU 3.00GHz | |
| Platform | Socket 478 | |
| CPU Type | Original OEM processor | |
| Number(Logical) | 2 | |
| Hyper-Threading | 2 | |
| Family | F | |
| FamilyEx | 00 | |
| Model | 4 | |
| Stepping | 1 | |
| APIC | 00 | |
| Feature | MMX SSE SSE2 HTT | |
| | Current | Original |
| Clock | 3014.53 MHz | 3000.00 MHz |
| System Clock | 200.97 MHz | 200.00 MHz |
| System Bus | 803.87 MHz | 800.00 MHz |

Device

| | |
|----------------|--|
| ChipSet | Intel 875P (Canterwood) |
| North | Intel 875P |
| South | Intel 82801EB/ER (ICH5/R) |
| IDE Controller | Intel(R) 82801EB Ultra ATA Storage Controllers |

Graphics

| | |
|---------------|-----------------|
| Video | ATI RADEON 9500 |
| Video Product | RADEON 9500 |

| | |
|----------------|--|
| Video Vendor | ATI Technologies Inc. |
| Video Chip | ATI Radeon Graphics Processor AGP (0x4144) |
| Video RAM | 128 MB |
| Driver Version | 6.14.10.6683 |
| Driver Date | 2007/03/15 |

HDD

| Type | Size | Model | Buffer | Mode |
|------|---------|-------------------------|--------|----------|
| SATA | 164.6GB | Hitachi HDS721616PLA380 | 7384KB | SATA/300 |
| SATA | 80.0GB | ST380013AS | 8192KB | SATA/150 |